

Výpis podrobných a hlavních bodů

Bod	Staničení	Y	X	Z	Celková délka	Typ	Směrník:	Poloměr
1	0	773075,483	1053847,032	253,27	0	ZU, V	10,896	-
2	5	773074,631	1053842,105	253,51	5		10,896	-
3	10	773073,78	1053837,178	253,75	10		10,896	-
4	15	773072,928	1053832,251	253,99	15		10,896	-
5	20	773072,076	1053827,324	254,23	20		10,896	-
6	22,78	773071,603	1053824,587	254,36	22,78	ZZ	10,896	-
7	25	773071,225	1053822,397	254,48	25		10,896	-
8	28,62	773070,608	1053818,828	254,7	28,62	V	10,896	-
9	30	773070,373	1053817,47	254,8	30		10,896	-
10	34,47	773069,612	1053813,068	255,15	34,47	KZ	10,896	-
11	35	773069,522	1053812,544	255,2	35		10,896	-
12	40	773068,67	1053807,617	255,63	40		10,896	-
13	45	773067,819	1053802,69	256,07	45		10,896	-
14	48,13	773067,285	1053799,602	256,34	48,13	ZZ	10,896	-
15	50	773066,967	1053797,763	256,53	50		10,896	-
16	51,74	773066,671	1053796,048	256,75	51,74	V	10,896	-
17	55	773066,116	1053792,836	257,27	55		10,896	-
18	55,35	773066,057	1053792,495	257,34	55,35	KZ	10,896	-
19	60	773065,264	1053787,909	258,22	60		10,896	-
20	61,9	773064,941	1053786,039	258,58	61,9	KU, V	10,896	-